




ARRANGE METHOD:



- Remark:**
- ① Cable: Cat. 6A S/FTP, Stranded Bare Copper, 4Pairs Wires, 26AWG, Jacket LSOH, OD: 6.5mm.
 - ② Plug: Cat. 6A Shielded Type Plug with 3 Prongs, 50u", 8P8C, UL94-V2, Mating Cycle >1200.
 - ③ Packing: IPC/PE Bag with Label.
 - ④ Printing: As your requirements.
- Testing: 100% Cat. 6A Component Test.
All materials are RoHS compliant.

| CUT LINE AND ARRANGE CRITERION | | | | CUT LINE AND ARRANGE CRITERION | | | |
|--------------------------------|-------------------|------------------------|----------------|--------------------------------|-------------------|------------------------|----------------|
| No. | Total Length (MM) | no. of patch cord (MM) | Cable Tie (MM) | No. | Total Length (MM) | no. of patch cord (MM) | Cable Tie (MM) |
| 1 | 300 | A | / | 19 | 13000 | | 175 |
| 2 | 500 | / | / | 20 | 14000 | | 180 |
| 3 | 1000 | / | 60 | 21 | 15000 | | 205 |
| 4 | 1500 | 175 | 70 | 22 | 16000 | | 210 |
| 5 | 2000 | | 75 | 23 | 17000 | | 215 |
| 6 | 2500 | | 80 | 24 | 18000 | | 220 |
| 7 | 3000 | 185 | 95 | 25 | 19000 | | 225 |
| 8 | 3500 | | 100 | 26 | 20000 | | 235 |
| 9 | 4000 | | 110 | 27 | 25000 | 120 | 265 |
| 10 | 5000 | | 120 | 28 | 30000 | | 315 |
| 11 | 6000 | | 130 | 29 | 40000 | | 365 |
| 12 | 7000 | | 135 | 30 | 50000 | | 415 |
| 13 | 7500 | 135 | 140 | 31 | 60000 | | 465 |
| 14 | 8000 | | 145 | 32 | 70000 | | 515 |
| 15 | 9000 | | 150 | 33 | 80000 | | 565 |
| 16 | 10000 | | 165 | 34 | 90000 | | 615 |
| 17 | 11000 | | 170 | 35 | 100000 | | 665 |
| 18 | 12000 | 120 | 175 | 36 | | | |

| WIRE CONNECTION TABLE | | | | | | | | | | LENGTH | | MOLD NO. | |
|-----------------------|--------------|------|-------------|------|--------------|--------------|--------------|--|--|--------|--|----------|--|
| white/ orange | white/ green | blue | white/ blue | blue | white/ green | white/ brown | white/ brown | | | | | | |
| A1 | A2 | A3 | A4 | A5 | A6 | A7 | A8 | | | | | | |
| B1 | B2 | B3 | B4 | B5 | B6 | B7 | B8 | | | | | | |

| | | | | | | | |
|-------------------------------|--|---------|--|----------------|--|--|--|
| DWG. NO. | | | | P6ASSB102B-003 | | | |
| TITLE | | | | | | | |
| CAT. 6A S/FTP EASY PATCH CORD | | | | | | | |
| UNIT | | SCALE | | SHEET | | | |
| mm | | 1/1 | | 1/1 | | | |
| DRAWN DATE | | PROJ. | | REV | | | |
| 2017/10/10 | | CHECKED | | 1 | | | |
| APPROVAL | | DRAWN | | | | | |
| Carine | | Wuming | | CathyLi | | | |